



ACN 062202242 Ph:(02) 66 884 - 188

Installation

- It is recommended our flooring be installed by an Accredited Timber Floor Installer. (eg. Floating or Glue Down using an appropriate polyurethane based adhesive).
- Floating Bamboo Floors can be protected, by using plastic waterproof underlay, to reduce rising damp & provide soundproofing.
- Our Bamboo Flooring can be laid over any sound level surface eg; tiles, old flooring, concrete and particleboard.
- Before gluing down Bamboo Flooring to concrete, the concrete should be moisture tested, and if necessary protected by applying a waterproof sealer to concrete slab, prior to floor installation to reduce rising damp.
- When gluing to slab, the slab should be level, sound & dry.
- Expansion gap of 10 mm to be maintained to perimeter of floor.
- Our T&G Bamboo Flooring is pre-finished, allowing quick & easy installation without mess, disruption or toxic fumes.
- Any excess glue must be thoroughly removed during installation.
- Flooring to be unpacked on site 7 days prior to lying. (Atmospheric Stabilisation).

Warranty

- Our flooring uses "Teffert" UV cured lacquer coating with 7 layers on top 1 coat to sides & bottom. Our T&G Bamboo Flooring comes with a 10 year (Residential) & 5 year (Commercial) for structural and surface finish warranty.

Care and Maintenance

- Our Bamboo flooring is low maintenance, however; Protection pads should be applied to all contact points of furniture to flooring.
- Wipe up all water spillage immediately.
- Protect flooring from direct sunlight.
- Regularly sweep or vacuum floor.
- Mop floors with Damp Mop only. Floor not to be saturated with water when cleaning.